



Description

Slim Type with more Practicability and Convenience

GZMI-100-5R is an hardened 5-port Industrial Ethernet Switch, provides non-blocking wire-speed performance in harsh industrial environment. It also provides 5-port 10/100/100BASE-TX RJ45 copper interfaces delivered in an IP40 rugged, strong case with redundant power system. Its slim case is suitable for such applications as surveillance system deployments, control management and wireless service in climatically demanding environments with wide temperature range from -40°C to 85°C.

The series provides the flexibility to all kinds of 10/100Mbps Ethernet Media on RJ-45 port and performs highly stable fiber performance.

The series is packaged in a compact IP40 case that allows either DIN rail or panel mounting to have efficient usage of cabinet space. It provides an integrated power supply with a wide range of voltages for worldwide operation. It also offers dual-redundant, reversible polarity 12V DC to 52V DC power supply inputs for high availability applications requiring dual or backup power inputs.

Features

- ❖ 5-port 10/100Base-Tx RJ-45 with auto negotiation and auto-MDI/MDI-X function
- ❖ 12V to 52V DC, redundant power input
- ❖ -40°C to 85°C operating temperature
- ❖ IP40 aluminum housing
- ❖ Supports 6KV DC Ethernet ESD protection
- ❖ Supports 6KV DC EFT protection for power line
- ❖ Free Fall, Shock and Vibration Stability
- ❖ DIN-rail and wall-mountable hardware design

Specification

Model No.	GZMI-100-5R
10/100BASE-TX Port	5 port RJ-45 auto-MDI / MDI-X

Shenzhen GZCOM Communication Co., Ltd.

Email: sales@gzcomm.com
<https://www.gzcomm.com>

Performance Specification	<p>Bandwidth: 1.6Gbps</p> <p>Packet Buffer Memory: 1Mbit</p> <p>Packet Forwarding Rate: 1.2Mpps</p> <p>MAC Address Table: 2K</p>
Installation	DIN rail
Maximum Frame Size	9000bytes packet size
Flow Control	Back pressure for half duplex, IEEE 802.3x pause frame for full duplex
Enclosure	IP40 aluminum housing
LED Indicator	<p>Power: Red</p> <p>Ethernet: Yellow</p> <p>POE: Green</p>
Power Input	12 to 52V DC redundant power
Power Consumption	3 watts max
Surge protection	±4KV
Network Protocols	<p>IEEE802.3 10BASE-T;</p> <p>IEEE802.3i 10Base-T;</p> <p>IEEE802.3u;100Base-TX/FX;</p> <p>IEEE802.3ab 1000Base-T;</p> <p>IEEE802.3z 1000Base-X;</p> <p>IEEE802.3x;</p>
Network cables	<p>10BASE-T: Cat3,4,5 UTP(≤100 meter)</p> <p>100BASE-TX: Cat5 or later UTP(≤10meter)</p> <p>1000BASE-TX: Cat6 or later UTP(≤100 meter)</p>
Industry Standard	<p>FCC CFR47 Part 15,EN55022/CISPR22, Class A</p> <p>IEC61000-4-2 (ESD): ±8kV (contact), ±12kV (air)</p> <p>IEC61000-4-3 (RS): 10V/m (80~1000MHz)</p> <p>IEC61000-4-4 (EFT): Power Port: ±4kV; Data Port: ±2kV</p> <p>IEC61000-4-5 (Surge): Power Port: ±2kV/DM, ±4kV/CM; Data Port: ±2kV</p>

	GZ5521-DC	DC 52V/1A, suitable for 1-Port PoE Industrial switch, or non-PoE Industrial switch
--	-----------	--

GZCOM reserves the right to make changes to the products or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such products or information.

Published by Shenzhen GZ Communication Co., Ltd.

Copyright ©GZCOM

All Rights Reserved